

## Compact Spring Rewind Reels



The 4000 & 5000 Series hose reels are durable and compact and are used for a wide variety of applications where space requirements are critical. The standard low pressure hose reel is for air or water service only. The medium and high pressure reels are for oil and grease respectively.

Model	I.D		O.D		Length		Pressure		Connection		Weight		Models		Pressure		Weight	
With hose	mm	Inch	mm	mm	m	ft	Bar	PSI	Inlet	Outlet	With hose	Without hose	Bar	PSI	Without hose	Without hose	Without hose	
<b>4000 Low Pressure Air &amp; Water</b>																		
4420 OLP 106	6	1/4	13	6	20	21	300	3/8"	1/4"	9Kg	4400 OLP 106	35	500	8Kg				
4425 OLP 106	6	1/4	13	8	25	21	300	3/8"	1/4"	9Kg	4400 OLP 106	35	500	8Kg				
4435 OLP 106	6	1/4	13	11	35	21	300	3/8"	1/4"	10Kg	4400 OLP 106	35	500	8Kg				
4617 OLP 106	10	3/8	16	5	17	21	300	3/8"	1/4"	9Kg	4600 OLP 106	35	500	8Kg				
4625 OLP 106	10	3/8	16	8	25	21	300	3/8"	1/4"	9Kg	4600 OLP 106	35	500	8Kg				
<b>5000 Low Pressure Air &amp; Water</b>																		
5450 OLP 106	6	1/4	14	15	50	21	300	3/8"	1/4"	12Kg	5400 OLP 106	35	500	9Kg				
5635 OLP 106	11	3/8	20	11	35	21	300	3/8"	1/4"	17Kg	5600 OLP 106	35	500	10Kg				
A5825 OLP 106	12	1/2	21	8	25	21	300	3/8"	1/2"	14Kg	A5800 OLP 106	35	500	10Kg				
<b>5000 Medium Pressure Air, Water &amp; Oil</b>																		
5435 OMP 106	6	1/4	15	11	35	190	2750	3/8"	1/4"	14Kg	5400 OMP 106	207	3000	20Kg				
5630 OMP 106	10	3/8	20	9	30	155	2250	3/8"	3/8"	14Kg	5600 OMP 106	207	3000	21Kg				
<b>5000 High Pressure Grease</b>																		
5430 OHP 106	6	1/4	15	9	30	345	5000	1/4"	1/4"	14Kg	5400 OHP 106	345	5000	12Kg				
5625 OHP 106	10	3/8	20	8	25	276	4000	1/4"	1/4"	14Kg	5600 OHP 106	345	5000	12Kg				
<b>DIMENSIONS 4000</b> W 136 mm L 321 mm H 327 mm																		
<b>DIMENSIONS 5000</b> W 152 mm L 343 mm H 368 mm																		



# Industrial Spring Rewind Reels



The 5005 Series is similar to the 4000 and 5000 Series except it handles longer hose lengths up to 15m. The quiet speed latch mechanism offers quiet operation combined with latch cam technology insuring longer latching life and trouble free performance. Reels are all-steel construction and compact for applications with critical space requirements. The medium and high pressure reels are for oil and grease respectively.

## Applications

- Industrial
- Automotive Centres
- Garages
- Service Vehicles
- Farms/Agricultural
- Fleet Maintenance
- Woodworking
- Workshop
- Aircraft Maintenance
- Pneumatic Tools
- Assembly Lines and many more

Model	I.D		O.D		Length		Pressure		Connection		Weight	Models	Pressure		Weight
With hose	mm	Inch	mm	m	ft	Bar	PSI	Inlet	Outlet	With hose	Without hose	Bar	PSI	Without hose	
<b>5005 &amp; 5006 Low Pressure Air &amp; Water</b>															
5650 OLP 106	10	3/8	16	15	50	21	300	3/8"	1/4"	12Kg	5605 OLP 106	35	500	14Kg	
A5835 OLP 106	12	1/2	20	11	35	21	300	3/8"	3/8"	18Kg	A5805 OLP 106	35	500	15Kg	
A5850 OLP 106	12	1/2	20	15	50	21	300	3/8"	1/2"	20Kg	A5806 OLP 106	35	500	15Kg	
<b>5005 Medium Pressure Air, Water &amp; Oil</b>															
A5835 OMP 106	12	1/2	21	11	35	138	2000	3/8"	1/2"	19Kg	A5805 OMP 106	207	3000	14Kg	
<b>5005 High Pressure Grease</b>															
5435 OHP 106	6	1/4	15	11	35	345	5000	1/4"	1/4"	19Kg	5405 OHP 106	345	5000	14Kg	
<b>Dimensions 5005</b>	W 152 mm		L 419 mm		H 445 mm										
<b>Dimensions 5006</b>	W 178 mm		L 419 mm		H 445 mm										

