



Fry's Napa AutoCare Center, Columbia City, IN



7850 OLP

Spring Driven Air/Water/Oil/Grease

Series 7000 - 1/4", 3/8", 1/2", 3/4" I.D.


Series 7000 is very robust and ideal for the most demanding applications. The reel's base and guide arms are formed from high-grade steel and engineered with structural forms and gussets to yield the greatest amount of strength. The standard low pressure hose is for air or water service only. The basic reel without hose can be used for air, water or oil. Consult Reelcraft for other products and hoses.



APPLICATIONS

- Industrial
- Automotive Service Centers
- Transmission Shops
- Fleet Maintenance Facilities
- Pneumatic Tools
- Aircraft Maintenance
- Tire Stores
- Agriculture
- Farm & Ranch
- Service Trucks
- Wash Down
- Air & Water

Series 7000 E reels are the same as 7000 O reels except **E Series reels are fully enclosed**. To order, change the model number suffix letter O to E. Example, 7650 OHP becomes 7650 EHP. Add 17 lbs. to open reel weight.



DIMENSIONS

| | 7000 O | | 7000 E | |
|----------|--------------------------------|---------|--------------------------------|---------|
| | in / mm | in / mm | in / mm | in / mm |
| A | 20 ¹ / ₄ | 521 | 20 ³ / ₄ | 527 |
| B | 19 | 483 | 20 ³ / ₄ | 527 |
| C | 7 ⁷ / ₈ | 200 | 7 ⁷ / ₈ | 200 |
| D | 3 ⁷ / ₈ | 98 | 3 ⁷ / ₈ | 98 |
| E | 7 | 178 | 8 | 204 |

Four 1/2" (12.7mm) diameter mounting holes.

For all metric thread connections over 1/2" add the suffix number 70 to indicate BSPT threads - example 7900 OLP70.

| MODELS WITH HOSE | | | | HOSE CAPACITY | | | | MODELS WITHOUT HOSE | | |
|--|----------|-----------|---------|---------------|---------|---------|--------|---------------------|----------|-----------|
| MODEL | WEIGHT | PRESSURE | I.D. | O.D. | (M)NPTF | (F)NPTF | LENGTH | MODEL | WEIGHT | PRESSURE |
| | lbs / kg | psi / bar | | | OUTLET | INLET | | | lbs / kg | psi / bar |
| | | | in / mm | in / mm | in | in | ft / m | | | |
| LOW PRESSURE AIR /WATER REELS* Maximum Temperature 150° F (65° C) | | | | | | | | | | |
| 7650 OLP | 47 22 | 300 21 | 3/8 10 | .688 18 | 1/4 | 1/2 | 50 15 | 7600 OLP | 42 19 | 500 35 |
| 7670 OLP | 50 23 | 300 21 | 3/8 10 | .688 18 | 1/4 | 1/2 | 70 22 | 7600 OLP | 42 19 | 500 35 |
| 7850 OLP | 51 24 | 300 21 | 1/2 13 | .844 22 | 3/8 | 1/2 | 50 15 | 7800 OLP | 43 20 | 500 35 |
| 7925 OLP | 49 22 | 250 17 | 3/4 19 | 1.188 31 | 3/4 | 3/4 | 25 8 | 7900 OLP | 44 20 | 500 35 |
| F7925 OLP [§] | 53 24 | 50 3.5 | 3/4 19 | 1.188 31 | 3/4 | 3/4 | 25 8 | F7900 OLP | 45 21 | 500 35 |
| MEDIUM PRESSURE OIL REELS** Maximum Temperature 210° F (99° C) | | | | | | | | | | |
| 7650 OMP | 55 25 | 2250 158 | 3/8 10 | .690 18 | 1/2 | 1/2 | 50 15 | 7600 OMP | 45 21 | 3000 207 |
| 7850 OMP | 57 26 | 2000 141 | 1/2 13 | .815 21 | 1/2 | 1/2 | 50 15 | 7800 OMP | 42 19 | 3000 207 |
| HIGH PRESSURE GREASE REELS*** Maximum Temperature 210° F (99° C) | | | | | | | | | | |
| 7450 OHP | 57 26 | 5000 345 | 1/4 6 | .590 17 | 1/4 | 1/2 | 50 15 | 7400 OHP | 43 20 | 5000 345 |
| 7650 OHP | 60 27 | 4000 276 | 3/8 10 | .750 19 | 1/4 | 1/2 | 50 15 | 7600 OHP | 46 21 | 5000 345 |

*Low pressure reels furnished standard with PVC hose. **Medium pressure reels furnished standard with S.A.E. 100 R1T one wire braid hose. ***High pressure reels furnished standard with S.A.E. 100 R2T Two wire braid hose, suitable for grease or hydraulic oil applications only.
 § Series F7925 OLP supplied with fuel grade hose and UL330 & UCL approved hose with a 250 psi (17 bar) minimum burst.
 See page 55 for inlet hose assemblies and adjustable bumper stops. **See page 53 for optional mounting bases and brackets.**