

Welding & Cutting Reels



Reels for Oxy / acetylene & oxy / propane

ReCoila® 's welding and cutting reels are engineered to improve safety and reduce the risk of tripping hazards within the working environment.

Model	ID		OD		Length		Weight	Model	ID		Length		Weight
with hose	mm	inch	mm	mm	ft	with hose	without hose	mm	inch	m	ft	without hose	
TW Range - 20 Bar													
TW5425 OLP 106	6	1/4	14	7.5	25	14	TW5400 OLP 106	6	1/4	7.5	25	9	
TW7450 OLP 106		1/4	14	15	50	26	TW7400 OLP 106	6	1/4	18	60	19	
TW84100 OLPT 106		1/4	30	30	100	48	TW84000 OLPT 106	6	1/4	30	100	36	
TW86075 OLPT 106		3/8	22	23	75	45	TW86000 OLPT 106	10	3/8	23	75	39	
Manual Reel Sold Without Hose							BA36106 L 106	6	1/4	38	125	22	
Manual Reel Sold Without Hose							BA36112 L 106	6	1/4	76	250	25	

Twin Hydraulic Reels



Dual Inlet Reels

The dual inlet series of reels incorporates contemporary engineering and manufacturing techniques to give trouble free performance.

Used for low, medium and high pressure applications, where dual hose is required. Both ranges are constructed from heavy duty steel and features high quality full flow dual fluid paths and locking mechanisms.

Model	ID		OD		Length		Weight	Model	OD	Length		Weight	Connections	
with twin hose	mm	inch	mm	m	ft	with hose	without hose	mm	m	ft	without hose	inlet	outlet	
TH Range - 207 Bar														
TH5425 OMP 106	6	1/4	13	7.5	25	15	TH5400 OMP 106	13	8	25	9	1/4"	1/4"	
TH7445 OMP 106	6	1/4	13	14	45	30	TH7400 OMP 106	13	15	45	19	1/4"	1/4"	
TW7630 OMP 106	10	3/8	16	9	30	27	TH7600 OMP 106	16	9	30	19	3/8"	3/8"	
TW86050 OMP 106	10	3/8	16	15	50	45	TH86000 OMP 106	16	15	50	36	3/8"	3/8"	
TW88050 OMP 106	12	1/2	23	15	50	47	TH88000 OMP 106	23	15	50	39	1/2"	1/2"	

