

Twin Pedestal Spring Rewind Reels



The 530, 540 & 560 Series are extremely durable, high quality steel hose reels that will suit hose size ranging from 12mm id (1/2") up to 25mm id (1"). Sturdy and compact, the SE Range allows the user to manage hose safely, practically and effectively. The SE Range is available with or without hose and is suitable for numerous applications.

Models		ID		OD	Length		Pressure		Connection		Weight	Dimensions in mm		
With Hose	Without Hose	mm	inch	mm	m	ft	Bar	PSI	Inlet	Outlet	With Hose	W	L	H
Low Pressure Air & Water														
	SE530-10	12	1/2	20	25	82	20	300	1/2"	1/2"	19Kg	203	560	550
SE530-12		12	1/2	20	25	82	20	300	1/2"	1/2"	25Kg	203	560	550
	SE540-10	19&25	3/4&1	25&35	20&15	65&50	20	300	1"	1"	24Kg	300	560	550
SE540-12		19	3/4	25	20	66	20	300	1"	3/4"	35Kg	300	560	550
SE540-13		25	1	35	15	50	20	300	1"	1"	37Kg	300	560	550
	SE560-10	19&25	3/4&1	25&32	30	100	20	300	1"	1"	30Kg	488	578	522
SE560-11		19	3/4	25	30	100	20	300	1"	3/4"	50Kg	488	578	522
SE560-15		25	1	32	30	100	20	300	1"	1"	60Kg	488	578	522
Medium Pressure Hot Water 150°C														
	SE530-20	12	1/2	19	25	82	100	1500	1/2"	1/2"	19Kg	203	560	550
SE530-22		12	1/2	19	25	82	100	1500	1/2"	1/2"	32Kg	203	560	550
	SE540-20	19&25	3/4&1	25&35	20&30	62&100	100	1500	1"	1"	24Kg	300	560	550
SE540-23		19	3/4	25	20	66	100	1500	1"	3/4"	37Kg	300	560	550
	SE540-25	12	1/2	20	30	100	100	1500	1/2"	1/2"	24Kg	300	560	550
SE540-26		12	1/2	20	30	100	100	1500	1/2"	1/2"	38Kg	300	560	550
	SE560-20	19&25	3/4&1	25&32	30	100	100	1500	1"	1"	30Kg	488	578	522
SE560-21		19	3/4	25	30	100	100	1500	1"	3/4"	55Kg	488	578	522
SE560-25		25	1	32	30	100	100	1500	1"	1"	60Kg	488	578	522
High Pressure Hot Water 150°C														
	SE530-30	10	3/8	18	25	82	200	3000	3/8"	1/2"	19Kg	203	560	550
SE530-31		10	3/8	18	25	82	200	3000	3/8"	3/8"	30Kg	203	560	550
	SE540-30	10	3/8	18	30	100	200	3000	3/8"	1/2"	24Kg	300	560	550
SE540-31		10	3/8	18	30	100	200	3000	3/8"	3/8"	40Kg	300	560	550
	SE560-30	10	3/8	18	30	100	200	3000	3/8"	1/2"	30Kg	488	578	522
SE560-32		10	3/8	18	50	165	200	3000	3/8"	3/8"	75Kg	488	578	522

